

Gold Mount Battery

- Li-ion rechargeable battery, no memory effect.
- 4-level LED power indicator.
- Built-in intelligent management & capacity management circuit.
- Supply power to camera light by the standard Power Tap port.
- Compatible with all the broadcast video cameras using Gold Mount battery pack.

V Lock Battery

- Li-ion rechargeable battery, no memory effect.
- 4-level LED power indicator.
- Built-in intelligent management & capacity management circuit.
- Supply power to camera light by the standard Power Tap port.
- Compatible with all the broadcast video cameras using V Lock battery pack.



Model	Voltage	Capacity	Operation temperature	Dimensions	weight
ET-AN65	14.8V	65Wh	-30°C~+55°C	153x102x41mm	500g
ET-AN95	14.8V	95Wh	-30°C~+55°C	153x102x46mm	730g
ET-AN130	14.8V	130Wh	-30°C~+55°C	153x102x58mm	930g
ET-AN160	14.8V	160Wh	-30°C~+55°C	153x102x58mm	1125g
ET-AN190	14.8V	190Wh	-30°C~+55°C	153x102x68mm	1400g

Model	Voltage	Capacity	Operation temperature	Dimensions	weight
ET-65S	14.8V	65Wh	-30°C~+55°C	153x102x36mm	500g
ET-95S	14.8V	95Wh	-30°C~+55°C	153x102x43mm	730g
ET-130S	14.8V	130Wh	-30°C~+55°C	153x102x54mm	930g
ET-160S	14.8V	160Wh	-30°C~+55°C	153x102x54mm	1125g
ET-190S	14.8V	190Wh	-30°C~+55°C	153x102x63mm	1400g